



You Power The Life
www.elerix.com

Technical specification

ELERIX EX-L230

High Energy
Density
Storage LFP
Cell


LiFePo4

Lithium Iron Cell

VDA PLUS 174/204

3.2V / 230Ah / 1C / MODEX

EX-L230



- ▶ High Energy Density Cell - 1C - 230A Discharge
- ▶ Lithium Iron Phosphate - LiFePO4 Chemistry
- ▶ Long Cycle and Calendar Life (3000 cycles / 15 years)
- ▶ Only Plus Temperature Range, No-Frost
- ▶ Superior quality and safety. No toxic chemicals
- ▶ MODEX type M8 terminals

ELERIX EX-L230

LiFePO₄, Lithium Iron Cell
3.2V / 280Ah / 1C



ELECTRICAL CHARACTERISTICS

Items	Specification	Remarks		
Product code	EX-L230			
Nominal Voltage (V)	3.2			
Nominal Capacity (Ah)	230	Charge @0.5C Discharge @0.5C		
Nominal Energy (Wh)	736			
Form Factor				
Terminal type	MODEX Terminal with M8 Hole			
Terminal material	Alu (-) / Alu (+)			
Cell Dimension (mm)	Width	174		
	Height	204	Without terminals	
	Thick	54		
Cell Volume (dm ³ - L)	1.92			
Nominal Weighth (kg)	4.1	Average value		
Energy Density	Gravity (Wh/kg)	180		
	Volume (Wh/L)	384		
Internal Resistance mOhm (Max)	0.5			
Voltage	Minimal (V)	2.5		
	Maximal (V)	3.75		
Current	Charge	Standard (A)	115	
		Max. Cont. (A)	230	
	Discharge	Standard (A)	115	
		Max. Cont. (A)	230	Continued, temp ≤ 50°C
		Peak (A)	345	≤ 30 sec, temp ≤ 50°C
Cycle Life at 80% DOD	3000	@0.3C/1C, @25°C, >80% SOH		
Operating Lifespan (Calendar Life)	15 years	Average material aging estimation		
Operating Temperature	Charge (°C)	0 ≈ +50 °C		
	Discharge (°C)	-20 ≈ +60 °C		
	Storage (°C)	-20 ≈ +45 °C		

KEY SAFETY FEATURES

Items	Specification
Fire	No Self-ignition, No Explosion.
Overcharge	No Explosion. No Fire.
Short-circuit	No Explosion. No Fire.
Penetration	Smoke only. No Fire.
Crush	Smoke only. No Fire.
Overheating	Stable up to +130°C. No fire.
Non-toxic	No Cobalt, No Lead-Acid.
Recycling	+90% Recyclable.

Are you interested in more details?
Visit our online presentation.

[PRODUCT WEBPAGE >](#)